CLAIMS

- An apparatus f r active in situ multi-element gas Claim 1. sparging for accelerated bioremediation or for removal of 2 c ntaminants in a soil formati n containing a subsurface groundwater aquifer, the multi-gas contained in bubbles, said apparatus comprising;
- 6 a) a plurality of injection wells each having casing means extending to a depth of a selected aquifer;
- 8 b) means for providing an oxidizing agent;
 - c) means for sizing bubbles;

12

26

- 10 d) means for controlled mixing of ambient air with said oxidizing agent;
 - e) means for controlled mixing of ambient air with said oxidizing agent comprising ozone to provide a multi-element gas;
 - f) means for injecting said multi-element oxidizing gas in said aquifer comprising a plurality of microporous diffusers, without applying a vacuum for extraction biodegration by-products, wherein said diffusers form micro-fine bubbles containing said multi-element gas that oxidizes in a gas/gas reaction, by stripping, chlorinated hydrocarbons from the aquifer; and
- 20 g) agitation means (pulsing or surging) for intermittently agitating water in the well effective to alter the path of microfine bubbles through a porous formation whereby enhanced contact 22 between the oxidizing agent contained in each said bubble by stripping pollutant from solution in ambient water into the mini-24 atmosphere of each bubble for gas/gas reaction is effective to
- increase the efficiency and speed of remediation of a site. Claim 2. The apparatus of claim 1 wherein the means for injecting
- multi-element oxidizing gas in said aquifer comprises a 2 microporous diffuser for producing bubbles configured to be a
- direct substitute for a well screen with 30% porosity 5-50 micron 4 channel size resistance to flow only 1 to 3 PSI, capable of
- handling high volume flow, in combination with a selected annular 6 pack means (sized to formation by means of a test means); said
- diffuser positioned on end of pipe riser means to reduce residence 8

time in the riser volume; wherein the size of the micro-fine 10 bubbles is as set forth in the following table; SIZE OF BUBBLES

12		UPWARD	TIME (MINUTES) FOR	
	BUBBLE	VELOCITY	UPWARDS MIGRATION	
14	DIAMETER	IN WATER	(3 METERS) (Coarse Sand and	Gravel)
	10mm	.25 m/s	19 min	:
16	2mm	.16 m/s	30 min	•
	.2mm	.018 m/s	240 min	

Claim 3. The apparatuses of claim 1 wherein the agitation means for 2 intermittently agitating water in the well effective to alter the path of micro-fine bubbles through a solid formation comprises a submersible pump

Claim 4. The apparatuses of claim 1 wherein the means for sizing micro-fine bubbles micro-fine bubbles containing encapsulated gas means comprises a fine bubble production chamber contained in said casing means of each injection well.

Claim 5. The apparatuses of claim 4 including the employment of specially-designed wellheads to equalize injected flow between formations of differing permeability.

Claim 6. The apparatuses of claim 4 including the use of 2 alternating pumpage and bubble injection to maximize dispersal of bubbles within and outward from specially-designed well casing

- An apparatus for active in situ multi-element gas Claim 7.
- 2 for bioremediation for removal contaminants in a soil sparging formation containing a subsurface groundwater aquifer, the multi-
- gas contained in bubbles, said apparatus comprising: 4

containing a fine bubble production chamber.

ڄڂ

- a) a plurality of injection wells extending to a depth of a 6 selected aquifer;
 - b) means for providing an oxidizing agent;
- 8 c) means for controlled mixing of ambient air with said oxidizing agent to provide a multi-element gas;
- 10 d) means for injecting said multi-element oxidizing gas in said aquifer comprising a plurality of microporous diffusers,

- without applying a vacuum for extraction biodegration by-products, wherein said diffusers form micro-fine bubbles containing said
- multi-element gas that ozidizes, by stripping, chlorinated hydrocarbons from the aquifer and surrounding saturated soil
- 16 formation into harmless by-products;

- e) agitation means for intermittently agitating water in the

 well effective to alter the path of micro-fine bubbles through a

 solid formation whereby enhanced contact between the oxidizing

 agent contained in each said bubble by stripping pollutant from
- agent contained in each said bubble by stripping pollutant from solution in ambient water into the mini-atmosphere of each bubble
- effective to increase the efficiency and speed of remediation of a site.

Claim 8. The system of claim 9 wherein the diffuser means comprises HDPE porous material with well fittings and pass-through design which allows individual pressure and flow control wherein horizontal sparging is permitted with even distribution of air bubbles.